






P20 INTERIOR USE ONLY

100-240V 50/60Hz

DRX1; 2-Circuit Track LED 4° Optic 15W





CONSTRUCTION MATERIALS:

A380 Aluminium, Glassfilled Polycarbonate

MOUNTING: 2-Circuit Track

WEIGHT: 1.2 kg

FINISH: Black RAL9005

MAX AMBIENT TEMPERATURE: 40°C **CEILING CLEARANCE:** n/a **CEILING CUT-OUT:** n/a **CEILING THICKNESS:** n/a

CONTROL

MOVEMENT TYPE: Handheld DIMMING OPTION:

Circuit Eutrac with 4° optic. Manufactured from A380 aluminium and glass-filled polycarbonate. Finished in black (RAL 9005). Voltage is 100-240V 50/60HZ. Luminaire has high-performance colour rendering of 90+ CRI. Luminaire can be rotated, with +/-165° movement through the pan axis and +/- 110° through the tilt axis, at a resolution of less than 1° in either axis. Movement is controlled using a handheld remote, and dimming is controlled using DMX. Recording and recalling of scenes as standard.

DRX1 2700K LED (10W for light source) compact spotlight for 2-

Product is ETL listed to UL1574 and CSA C22.2#9.0 standards.

PART NO.

DRX1.0037.US

PRODUCT SUMMARY

DRX1 Spotlight; USA; 100-240V 50/60Hz; 2~ Eutrac; 4° Optic; 2700K 90+CRI LED 10W; Black; Movement using Handheld Remote; Dimming using DMX Control

> T +44 (0)20 8404 2400 SALES@RCLIGHTING.COM F +44 (0)20 8286 6626 WWW.RCLIGHTING.COM

DMX












100-240V 50/60Hz

DRX1; 2-Circuit Track LED 4° Optic 15W



4°		1	LED
1m	0.07m	٨	56646 lx
		I	
2m	0.14m	Ш	14161 lx
		П	
3m	0.21m	П	6294 lx
		П	
4m	0.28m		3540 lx
5m	0.35m		2266 lx

Photometry

Cone Diagram

22°/s

MOVEMENT TYPE: Handheld PAN MOVEMENT RANGE: ±165° **TILT MOVEMENT RANGE:** ±110° PAN MOVEMENT RESOLUTION: TILT MOVEMENT RESOLUTION: < 10 PAN SPEED OF MOVEMENT: 24°/s

VOLTAGE REGION: 100-240V 50/60Hz

IEC PROTECTION CLASS: Class 2 LIGHT SOURCE WATTAGE: 10W MOVEMENT WATTAGE: 4W LUMINAIRE CIRCUIT WATTAGE: 15W

TILT SPEED OF MOVEMENT:

LIGHT SOURCE: LED

MIN. DISTANCE FROM TARGET:

MODULE LUMEN OUTPUT: 594LM ABSOLUTE LUMEN OUTPUT: 540LM **GLARE MECHANICAL CUT-OFF:** 25 GLARE COMFORT CUT-OFF: 50 **COLOUR TEMP:** 2700K

PART NO.

DRX1.0037.US

PRODUCT SUMMARY

DRX1 Spotlight; USA; 100-240V 50/60Hz; 2~ Eutrac; 4° Optic; 2700K 90+CRI LED 10W; Black; Movement using Handheld Remote; Dimming using DMX Control

> T +44 (0)20 8404 2400 SALES@RCLIGHTING.COM F +44 (0)20 8286 6626 WWW.RCLIGHTING.COM