

IP20 INTERIOR USE ONLY 100-240V 50/60Hz


DRX1; 2-Circuit Track

LED 4° Optic 15W





Lamp Diagram



Pan and Tilt



Product Render

PHYSICAL

CONSTRUCTION MATERIALS:	A380 Aluminium, Glass-filled Polycarbonate
MOUNTING:	2-Circuit Track
WEIGHT:	1.2 kg
FINISH:	Black RAL9005
MAX AMBIENT TEMPERATURE:	40°C
CEILING CLEARANCE:	n/a
CEILING CUT-OUT:	n/a
CEILING THICKNESS:	n/a

CONTROL

MOVEMENT TYPE:	Handheld
DIMMING OPTION:	DALI

SPECIFICATION

DRX1 2700K LED (10W for light source) compact spotlight for 2-Circuit Eutrac with 4° optic. Manufactured from A380 aluminium and glass-filled polycarbonate. Finished in black (RAL 9005). Voltage is 100-240V 50/60HZ. Luminaire has high-performance colour rendering of 90+ CRI. Luminaire can be rotated, with +/- 165° movement through the pan axis and +/- 110° through the tilt axis, at a resolution of less than 1° in either axis. Movement is controlled using a handheld remote, and dimming is controlled using external DALI dimming. Recording and recalling of scenes as standard. Product is ETL listed to UL1574 and CSA C22.2#9.0 standards.

PART NO. **DRX1.0039.US**

PRODUCT SUMMARY


DRX1 Spotlight; USA; 100-240V 50/60Hz; 2~ Eutrac; 4° Optic; 2700K 90+CRI LED 10W; Black; Movement using Handheld Remote; Dimming Using External DALI Control

T +44 (0)20 8404 2400 SALES@RCLIGHTING.COM
F +44 (0)20 8286 6626 WWW.RCLIGHTING.COM


IP20 INTERIOR USE ONLY 100-240V 50/60Hz

DRX1; 2-Circuit Track

LED 4° Optic 15W



Photometry



Cone Diagram

MOVEMENT

MOVEMENT TYPE:	Handheld
PAN MOVEMENT RANGE:	±165°
TILT MOVEMENT RANGE:	±110°
PAN MOVEMENT RESOLUTION:	<1°
TILT MOVEMENT RESOLUTION:	<1°
PAN SPEED OF MOVEMENT:	24°/s
TILT SPEED OF MOVEMENT:	22°/s

LIGHTING

LIGHT SOURCE:	LED
MIN. DISTANCE FROM TARGET:	
MODULE LUMEN OUTPUT:	594LM
ABSOLUTE LUMEN OUTPUT:	540LM
GLARE MECHANICAL CUT-OFF:	25
GLARE COMFORT CUT-OFF:	50
COLOUR TEMP:	2700K

ELECTRICAL

VOLTAGE REGION:	100-240V 50/60Hz
IEC PROTECTION CLASS:	Class 2
LIGHT SOURCE WATTAGE:	10W
MOVEMENT WATTAGE:	4W
LUMINAIRE CIRCUIT WATTAGE:	15W

PART NO. **DRX1.0039.US**

PRODUCT SUMMARY

DRX1 Spotlight; USA; 100-240V 50/60Hz; 2~ Eutrac; 4° Optic; 2700K 90+CRI LED 10W; Black; Movement using Handheld Remote; Dimming Using External DALI Control

T +44 (0)20 8404 2400 SALES@RCLIGHTING.COM
F +44 (0)20 8286 6626 WWW.RCLIGHTING.COM