








P20 INTERIOR USE ONLY

100-240V 50/60Hz

## DRX1; 2-Circuit Track LED 4° Optic 15W





CONSTRUCTION MATERIALS:

A380 Aluminium, Glassfilled Polycarbonate

MOUNTING: 2-Circuit Track

WEIGHT: 1.2 kg

FINISH: White RAL9010

40°C MAX AMBIENT TEMPERATURE: **CEILING CLEARANCE:** n/a **CEILING CUT-OUT:** n/a **CEILING THICKNESS:** n/a

MOVEMENT TYPE: DIMMING OPTION:

CONTROL

DMX

DMX

Circuit Eutrac with 4° optic. Manufactured from A380 aluminium 165° movement through the pan axis and +/- 110° through the tilt axis, at a resolution of less than 1° in either axis. Movement and dimming is controlled by DMX. Recording and recalling of scenes as standard. Product is ETL listed to UL1574 and CSA C22.2#9.0 standards.

PART NO.

DRX1.0043.US

PRODUCT SUMMARY

DRX1 Spotlight; USA; 100-240V 50/60Hz; 2~ Eutrac; 4° Optic; 3000K 90+CRI LED 10W; White; Movement & Dimming using DMX Control only

> T +44 (0)20 8404 2400 SALES@RCLIGHTING.COM F +44 (0)20 8286 6626 WWW.RCLIGHTING.COM












100-240V 50/60Hz

## DRX1; 2-Circuit Track LED 4° Optic 15W



4°		١	LED
1m	0.07m		56646 lx
		I	
2m	0.14m	П	14161 lx
		П	
3m	0.21m	П	6294 lx
		П	
4m	0.28m		3540 lx
5m	0.35m		2266 lx

Photometry

Cone Diagram

MOVEMENT TYPE: DMX PAN MOVEMENT RANGE: ±165° **TILT MOVEMENT RANGE:** ±110° PAN MOVEMENT RESOLUTION: TILT MOVEMENT RESOLUTION: < 10 PAN SPEED OF MOVEMENT: 24°/s TILT SPEED OF MOVEMENT: 22°/s

**VOLTAGE REGION:** 100-240V 50/60Hz

**IEC PROTECTION CLASS:** Class 2 LIGHT SOURCE WATTAGE: 10W MOVEMENT WATTAGE: 4W LUMINAIRE CIRCUIT WATTAGE: 15W

LIGHT SOURCE: LED

MIN. DISTANCE FROM TARGET:

MODULE LUMEN OUTPUT: 594LM ABSOLUTE LUMEN OUTPUT: 540LM **GLARE MECHANICAL CUT-OFF:** 25 GLARE COMFORT CUT-OFF: 50 **COLOUR TEMP:** 3000K

PART NO.

DRX1.0043.US

PRODUCT SUMMARY

DRX1 Spotlight; USA; 100-240V 50/60Hz; 2~ Eutrac; 4° Optic; 3000K 90+CRI LED 10W; White; Movement & Dimming using DMX Control only

> T +44 (0)20 8404 2400 SALES@RCLIGHTING.COM F +44 (0)20 8286 6626 WWW.RCLIGHTING.COM