

HYSICAL	WEIGHT:	Z
	FINISH:	Ĭ
	MAX AMBIENT TEMPERATURE:	FIC/
	CEILING CLEARANCE:	Ü
	CEILING CUT-OUT:	SP
	CEILING THICKNESS:	

MOVEMENT TYPE:


DIMMING OPTION:

CONTROL

PART NO.

PRODUCT SUMMARY





hoage not found or type unknown



Photometry

Cone Diagram

MOVEMENT TYPE: PAN MOVEMENT RANGE: TILT MOVEMENT RANGE: PAN MOVEMENT RESOLUTION: TILT MOVEMENT RESOLUTION: PAN SPEED OF MOVEMENT:

TILT SPEED OF MOVEMENT:

IEC PROTECTION CLASS:

VOLTAGE REGION: IEC PROTECTION CLASS LIGHT SOURCE WATTAGE: LIGHT SOURCE WATTAGE:

LUMINAIRE CIRCUIT WATTAGE:

U LIGHT SOURCE: MIN. DISTANCE F MODULE LUMEN MIN. DISTANCE FROM TARGET: MODULE LUMEN OUTPUT: ABSOLUTE LUMEN OUTPUT: GLARE MECHANICAL CUT-OFF: GLARE COMFORT CUT-OFF: COLOUR TEMP:

PART NO.

PRODUCT SUMMARY