

WEIGHT: **PHYSICAL** 

FINISH:

MAX AMBIENT TEMPERATURE:

**CEILING CLEARANCE:** 

CEILING CUT-OUT:

**CEILING THICKNESS:** 

MOVEMENT TYPE: DIMMING OPTION:


CONTROL

PART NO.



PRODUCT SUMMARY







Photometry

Cone Diagram

MOVEMENT TYPE:

PAN MOVEMENT RANGE:

TILT MOVEMENT RANGE:

PAN MOVEMENT RESOLUTION:

TILT MOVEMENT RESOLUTION:

PAN SPEED OF MOVEMENT:

TILT SPEED OF MOVEMENT:

IEC PROTECTION CLASS:

VOLTAGE REGION:

IEC PROTECTION CLASS

LIGHT SOURCE WATTAGE: LIGHT SOURCE WATTAGE:

LUMINAIRE CIRCUIT WATTAGE:

LIGHT SOURCE:
MIN. DISTANCE F
MODULE LUMEN

MIN. DISTANCE FROM TARGET:

MODULE LUMEN OUTPUT:

ABSOLUTE LUMEN OUTPUT:

GLARE MECHANICAL CUT-OFF:

GLARE COMFORT CUT-OFF:

COLOUR TEMP:

PART NO.



PRODUCT SUMMARY