




DRX5; Recessed - Standard Trim LED 10° Optic 20W









CONSTRUCTION MATERIALS:

LM24 Aluminium, Glassfilled Polycarbonate, Mild Steel mounting ring

MOUNTING:

Recessed - Standard

Trim

WEIGHT:

PHYSICA

1.55ka

FINISH:

Black RAL9005

CEILING CLEARANCE:

MAX AMBIENT TEMPERATURE:

40°C

CEILING CUT-OUT:

200mm

145mm

CEILING THICKNESS:

10-55mm

MOVEMENT TYPE:

DMX

DIMMING OPTION:

DMX

DRX5 3000K LED (17W for light source) standard trim recessed luminaire with 10° optic. Manufactured from LM24 aluminium and glass-filled polycarbonate, with a mild-steel mounting ring. Finished in black (RAL 9005). Voltage is 100-277V 50/60HZ. Luminaire has high-performance colour rendering of 90+ CRI. Luminaire can be rotated, with +/- 185° movement through the pan axis and +35 through the tilt axis, at a resolution of less than and glass-filled polycarbonate, with a mild-steel mounting ring. pan axis and +35 through the tilt axis, at a resolution of less than 1° in either axis. Movement and dimming is controlled by DMX. Recording and recalling of scenes as standard.

PART NO.

DRX5.0018

PRODUCT SUMMARY

DRX5 Spotlight; 100-277V 50/60Hz; Standard Trim Mounting; 10° Optic; 3000K 90+CRI LED 17W; Black; Movement & Dimming using DMX Control only

DAT-DRX5.0018

PAGE 1 OF 2

T +44 (0)20 8404 2400 SALES@RCLIGHTING.COM F +44 (0)20 8286 6626 WWW.RCLIGHTING.COM








100-277V 50/60Hz

DRX5; Recessed - Standard Trim LED 10° Optic 20W



10°		A.	LED
1m	0.17m	_ A	41654 lx
2m	0.35m	Λ	10414 lx
3m	0.52m		4628 lx
4m	0.70m		2603 lx
5m	0.87m		1666 lx

Photometry

Cone Diagram

MOVEMENT TYPE: DMX PAN MOVEMENT RANGE: ±185° TILT MOVEMENT RANGE: +35° PAN MOVEMENT RESOLUTION: <7° TILT MOVEMENT RESOLUTION: < 10 PAN SPEED OF MOVEMENT: 20°/s TILT SPEED OF MOVEMENT: 20°/s

VOLTAGE REGION: 100-277V 50/60Hz

IEC PROTECTION CLASS: Class 2 LIGHT SOURCE WATTAGE: 17W MOVEMENT WATTAGE: 3W LUMINAIRE CIRCUIT WATTAGE: 20W

LIGHT SOURCE: LED MIN. DISTANCE FROM TARGET: N/A MODULE LUMEN OUTPUT: 1573LM ABSOLUTE LUMEN OUTPUT: 1474LM 17° **GLARE MECHANICAL CUT-OFF:**

GLARE COMFORT CUT-OFF: 52° **COLOUR TEMP:** 3000K

PART NO.

DRX5.0018

PRODUCT SUMMARY

DRX5 Spotlight; 100-277V 50/60Hz; Standard Trim Mounting; 10° Optic; 3000K 90+CRI LED 17W; Black; Movement & Dimming using DMX Control only

> T +44 (0)20 8404 2400 SALES@RCLIGHTING.COM F +44 (0)20 8286 6626 WWW.RCLIGHTING.COM

PAGE 2 OF 2