




## DRX7; Recessed - Standard Trim LED 7° Optic 35W









**CONSTRUCTION MATERIALS:** 

LM24 Aluminium, Glassfilled Polycarbonate, Mild Steel mounting ring

MOUNTING:

**PHYSICA** 

Recessed - Standard

Trim

WEIGHT:

3.0ka

FINISH:

Black RAL9005

**CEILING CLEARANCE:** 

MAX AMBIENT TEMPERATURE:

40°C

250mm

**CEILING CUT-OUT:** 

195mm

**CEILING THICKNESS:** 

3-45mm

MOVEMENT TYPE:

Handheld

**DIMMING OPTION:** 

DMX

DRX7 2700K LED (25W for light source) standard trim recessed luminaire with 7° optic. Manufactured from LM24 aluminium and glass-filled polycarbonate, with a mild-steel mounting ring. Finished in black (RAL 9005). Voltage is 100-277V 50/60HZ. Luminaire has high-performance colour rendering of 90+ CRI. Luminaire can be rotated, with +/- 185° movement through the pan axis and  $+35^{\circ}$  through the tilt axis, at a resolution of less than 1° in either axis. Movement is controlled using a handheld remote, and dimming is controlled using DMX. Recording and recalling of scenes as standard.

PART NO.

**DRX7.0008** 

PRODUCT SUMMARY

DRX7 Spotlight; 100-277V 50/60Hz; Standard Trim Mounting; 7° Optic; 2700K 90+CRI LED 25W; Black; Movement using Handheld Remote; Dimming using DMX Control

**DAT-DRX7.0008** 

PAGE 1 OF 2

T +44 (0)20 8404 2400 SALES@RCLIGHTING.COM F +44 (0)20 8286 6626 WWW.RCLIGHTING.COM








100-277V 50/60Hz

## DRX7; Recessed - Standard Trim LED 7° Optic 35W



7°		LED
1m	0.1m	82,063 lx
2m	0.2m	20,515 lx
3m	0.4m	9,118 lx
4m	0.5m	5,128 lx
5m	0.6m	3,282 lx

Photometry

Cone Diagram

MOVEMENT TYPE: Handheld PAN MOVEMENT RANGE: +/-185° TILT MOVEMENT RANGE: +35° PAN MOVEMENT RESOLUTION: <10 TILT MOVEMENT RESOLUTION: < 10 PAN SPEED OF MOVEMENT: 20°/s

TILT SPEED OF MOVEMENT: 20°/s **VOLTAGE REGION:** 100-277V 50/60Hz

**IEC PROTECTION CLASS:** Class 2 LIGHT SOURCE WATTAGE: 25W MOVEMENT WATTAGE: 4W LUMINAIRE CIRCUIT WATTAGE: 35W

LIGHT SOURCE: LED

MIN. DISTANCE FROM TARGET: N/A

MODULE LUMEN OUTPUT: 2200LM ABSOLUTE LUMEN OUTPUT: 1904LM

**GLARE MECHANICAL CUT-OFF:** 18° GLARE COMFORT CUT-OFF: 53° **COLOUR TEMP:** 2700K

PART NO.

DRX7.0008

PRODUCT SUMMARY

DRX7 Spotlight; 100-277V 50/60Hz; Standard Trim Mounting; 7° Optic; 2700K 90+CRI LED 25W; Black; Movement using Handheld Remote; Dimming using DMX Control

> T +44 (0)20 8404 2400 SALES@RCLIGHTING.COM F +44 (0)20 8286 6626 WWW.RCLIGHTING.COM