




DR2; 3-Circuit Track LED 10° Optic 24W



PHYSICAL	MOUNTING:	3-Circuit Track
	WEIGHT:	1.61kg
	FINISH:	White RAL9010
	MAX AMBIENT TEMPERATURE:	40°C
	CEILING CLEARANCE:	N/A
	CEILING CUT-OUT:	N/A
	CEILING THICKNESS:	N/A


CONTROL	MOVEMENT TYPE:	DMX
	DIMMING OPTION:	DMX

SPECIFICATION DR2 3000K LED (20W for light source) spotlight for 3-Circuit Eutrac with 10° optic. Manufactured from LM24 aluminium and glass-filled polycarbonate. Finished in white (RAL 9010). Voltage is 220-240V 50/60HZ. Luminaire has high-performance colour rendering of 90+ CRI. Luminaire can be rotated, with +/- 160° movement through the pan axis and +/- 90° through the tilt axis, at a resolution of less than 1° in either axis. Movement and dimming is controlled by DMX. Recording and recalling of scenes as standard.


PART NO.

DR2.0025
PRODUCT SUMMARY
DAT-DR2.0025

DR2; 3-Circuit Track LED 10° Optic 24W



Photometry



Cone Diagram

MOVEMENT	MOVEMENT TYPE:	DMX	LIGHTING	LIGHT SOURCE:	LED
	PAN MOVEMENT RANGE:	±160°		MIN. DISTANCE FROM TARGET:	N/A
	TILT MOVEMENT RANGE:	±90°		MODULE LUMEN OUTPUT:	1300lm
	PAN MOVEMENT RESOLUTION:	<1°		ABSOLUTE LUMEN OUTPUT:	1100lm
	TILT MOVEMENT RESOLUTION:	<1°		GLARE MECHANICAL CUT-OFF:	9°
	PAN SPEED OF MOVEMENT:	30°/s		GLARE COMFORT CUT-OFF:	50°
	TILT SPEED OF MOVEMENT:		COLOUR TEMP:	3000K	
ELECTRICAL	VOLTAGE REGION:	220 - 240V 50/60Hz			
	IEC PROTECTION CLASS:	Class 1			
	LIGHT SOURCE WATTAGE:	20W			
	MOVEMENT WATTAGE:	4W			
	LUMINAIRE CIRCUIT WATTAGE:	24W			

PART NO.

DR2.0025
PRODUCT SUMMARY
DAT-DR2.0025