




DRX1; 1-Circuit Track LED 4° Optic 15W



PHYSICAL	CONSTRUCTION MATERIALS:	A380 Aluminium, Glass-filled Polycarbonate
	MOUNTING:	1-Circuit Track
	WEIGHT:	1.2 kg
	FINISH:	White RAL9010
	MAX AMBIENT TEMPERATURE:	40°C
	CEILING CLEARANCE:	N/A
	CEILING CUT-OUT:	N/A
CEILING THICKNESS:	N/A	


CONTROL	MOVEMENT TYPE:	DMX
	DIMMING OPTION:	DMX

SPECIFICATION DRX1 4000K LED (10W for light source) compact spotlight for 1-Circuit Eutrac with 4° optic. Manufactured from A380 aluminium and glass-filled polycarbonate. Finished in white (RAL 9010). Voltage is 100-240V 50/60HZ. Luminaire has high-performance colour rendering of 80+ CRI. Luminaire can be rotated, with +/- 165° movement through the pan axis and +/- 110° through the tilt axis, at a resolution of less than 1° in either axis. Movement and dimming is controlled by DMX. Recording and recalling of scenes as standard.


PART NO. **DRX1.0023**

PRODUCT SUMMARY	DRX1 Spotlight; 100-240V 50/60Hz; 1~ Eutrac; 4° Optic; 4000K 80+CRI LED 10W; White; Movement & Dimming using DMX Control only
------------------------	---

DRX1; 1-Circuit Track LED 4° Optic 15W



Photometry



Cone Diagram

MOVEMENT	MOVEMENT TYPE:	DMX	LIGHTING	LIGHT SOURCE:	LED
	PAN MOVEMENT RANGE:	±165°		MIN. DISTANCE FROM TARGET:	N/A
	TILT MOVEMENT RANGE:	±110°		MODULE LUMEN OUTPUT:	594LM
	PAN MOVEMENT RESOLUTION:	<1°		ABSOLUTE LUMEN OUTPUT:	540LM
	TILT MOVEMENT RESOLUTION:	<1°		GLARE MECHANICAL CUT-OFF:	25°
	PAN SPEED OF MOVEMENT:	24°/s		GLARE COMFORT CUT-OFF:	50°
	TILT SPEED OF MOVEMENT:	22°/s	COLOUR TEMP:	4000K	
ELECTRICAL	VOLTAGE REGION:	100-240V 50/60Hz			
	IEC PROTECTION CLASS:	Class 2			
	LIGHT SOURCE WATTAGE:	10W			
	MOVEMENT WATTAGE:	4W			
	LUMINAIRE CIRCUIT WATTAGE:	15W			

PART NO. DRX1.0023

PRODUCT SUMMARY DRX1 Spotlight; 100-240V 50/60Hz; 1~ Eutrac; 4° Optic; 4000K 80+CRI LED 10W; White; Movement & Dimming using DMX Control only